



**Manufacturing Standard
Specifications
Version: 100901
GEO 320-3060
Diatomaceous Earth
PHYSICAL PROPERTIES**

Bulk Density	43 Pound per Cubic Foot
Free Moisture	0 Percent
Wet Breakdown	<1 Percent
Dry Breakdown	<25 Percent
Oil Retention	>75 Percent
Water Retention	>100 Percent
Volatile Classification	LVM
Loss on Ignition @ 1000C	<6.33 Percent
PH	7.0
Hardness	80
Particle Count	8.0-10.0 million/pound

PARTICLE SIZING

>30 Mesh (0.600mm)	.3 Percent
<30 Mesh (0.600mm)>60 Mesh (0.250mm)	99.0 Percent
<60 Mesh (0.250 mm)	.7 Percent
<100 Mesh (0.150 mm)	0 Percent

CHEMICAL ANALYSIS

Silica (SiO ₂)	75.29 Percent
Aluminum (Al ₂ O ₃)	9.25 Percent
Iron (Fe ₂ O ₃)	2.90 Percent
Calcium (CaO)	1.86 Percent
Magnesium (MgO)	1.65 Percent
Potassium (K ₂ O)	1.57 Percent
Sodium (Na ₂ O)	0.14 Percent
Titanium Dioxide (TiO ₂)	0.55 Percent
Phosphorus (P ₂ O ₅)	0.45 Percent

MINERALOGICAL ANALYSIS

Major Components	Fuller's Earth
------------------	----------------

FREIGHT CLASSIFICATION

Crushed Clay in Bags - NMFC# 48170 - Class 50 – Harmonization Code 2508.20.0000

REGULATORY APPROVALS

This product is classified as processing aid and has Generally Recognized as Safe (GRAS) status from the Food and Drug Administration (FDA). Chemical Name: Fuller's Earth (CAS 8031-18-3).